

DESOTO, INC.
MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS, AND RELATED MATERIALS
(CAPPROVED BY US DEPARTMENT OF LABOR "ESSENTIALLY SIMILAR" TO FORM OSHA-20)
SECTION I

DESOTO, INC.
ADMINISTRATIVE AND RESEARCH CENTER

1700 S. MT. PROSPECT ROAD
DES PLAINES, ILLINOIS 60018

EMERGENCY TELEPHONE (312) 391-9000

DMS 2115-9431
Blue-Gloss

PRODUCT CLASS
POLYESTER

MANUFACTURERS CODE IDENTIFICATION
826X445

TRADE NAME
SUPER DESOTHANE DN 9431
GL BLUE

DATE OF PREPARATION 11/17/82

***** SECTION II-HAZARDOUS INGREDIENTS *****

INGREDIENT	% BY* WEIGHT	PPM	TLV	MG/CU.M	LEL	VAPOR PRESSURE @ 20 DEG C
CARBON BLACK	< 0.5			3.5	NA	NA
METHYL ETHYL KETONE	< 5.0	200		590	1.8	70
METHYL ISOBUTYL KETONE-SKIN	10.0	50		205	1.4	15
2-ETHOXYETHYL ACETATE-SKIN **	30.0	50		270	1.8	2.0
ETHYL ACETATE	5.0	400		1400	2.2	76
BUTYL ACETATE	10.0	150		710	1.7	8.0
ORGANO TIN COMPOUND-SKIN	< 0.1			0.1 AS SN	NA	NA

* PERCENT BY WEIGHT:
TO NEAREST 5%, PLUS OR MINUS 5%, FOR SUBSTANCES 5-95%;
<5.0 FOR SUBSTANCES 0.5-5.0%;
<0.5 FOR SUBSTANCES 0.0-0.5%.

** ACGIH NOTICE OF INTENDED CHANGE, 1982: TLV-TWA=5PPM NE = NOT ESTABLISHED
NA = NOT APPLICABLE

***** SECTION III-PHYSICAL DATA *****

PROPERTY	MEASUREMENT
BOILING RANGE	171.0 TO 313.0 DEG F. 77.0 TO 156.0 DEG C. @760 MM HG
VAPOR DENSITY	X HEAVIER LIGHTER THAN AIR
WEIGHT PER GALLON	8.9 LBS.
PERCENT VOLATILE BY VOLUME	68.8
EVAPORATION RATE	FASTER X SLOWER THAN ETHER

11/17/82

***** SECTION IV-FIRE AND EXPLOSION DATA *****

DOT CATEGORY FLAMMABLE LIQUID FLASH POINT 22.0 DEG F.
OSHA CATEGORY FLAMMABLE LIQUID-CLASS I B (CLOSED CUP) -5.6 DEG C.

LOWER EXPLOSIVE LIMIT SEE II

EXTINGUISHING MEDIA: USE NATIONAL FIRE PROTECTION ASSOCIATION CLASS B
EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).

UNUSUAL FIRE AND EXPLOSION HAZARDS: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE
FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY
EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.
SPECIAL FIRE FIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY
BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE
AUTO IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG
NOZZLES ARE PREFERABLE. WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS
AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN.

***** SECTION V-HEALTH HAZARD DATA *****

THRESHOLD LIMIT VALUE: SEE II (NOT ESTABLISHED FOR PRODUCT)

EFFECTS OF OVEREXPOSURE:

INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS
SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING GAIT,
CONFUSION, UNCONSCIOUSNESS OR COMA.

SKIN OR EYE CONTACT: PRIMARY IRRITATION.

OTHER HEALTH EFFECTS:

REPRODUCTIVE AND BLOOD DISORDERS AND BIRTH DEFECTS HAVE BEEN OBSERVED IN
TESTS ON LABORATORY ANIMALS WITH 2-METHOXYETHANOL, 2-ETHOXYETHANOL, AND
2-ETHOXYETHYL ACETATE. BECAUSE THIS PRODUCT CONTAINS AT LEAST ONE OF THESE
SOLVENTS, HANDLING PRECAUTIONS AS OUTLINED IN SECTIONS VIII AND IX SHOULD BE
CAREFULLY FOLLOWED TO AVOID OVEREXPOSURE.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION: REMOVE FROM EXPOSURE.
RESTORE BREATHING. KEEP WARM AND QUIET. NOTIFY A PHYSICIAN. SKIN CONTACT:
WASH AFFECTED AREAS WITH WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A
PHYSICIAN. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. CONSULT A PHYSICIAN.
INGESTION: CONSULT A PHYSICIAN.

***** SECTION VI-REACTIVITY DATA *****

STABILITY: UNSTABLE X STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):

HAZARDOUS DECOMPOSITION PRODUCTS:
PRODUCTS OF COMBUSTION ARE HAZARDOUS

HAZARDOUS POLYMERIZATION: MAY OCCUR X WILL NOT OCCUR

CONDITIONS TO AVOID:

11/17/82

***** SECTION VII-SPILL OR LEAK PROCEDURES*****

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

WASTE DISPOSAL METHODS: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

*****SECTION VIII-SPECIAL PROTECTION INFORMATION*****

RESPIRATORY PROTECTION:

IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS INDICATED IN SECTION II USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. IN CONFINED AREAS USE NIOSH APPROVED AIR LINE TYPE RESPIRATORS OR HOODS.

VENTILATION: WHERE EMPLOYEES MAY BE EXPOSED, PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS IN SECTION II BELOW RECOMMENDED (ACGIH) OR REGULATED (OSHA) LIMIT. WHERE EMPLOYEES WILL NOT BE EXPOSED, KEEP LEL IN SECTION II BELOW 25% OF LIMIT

PROTECTIVE GLOVES: BUTYL RUBBER PREFERRED. NEOPRENE OR NITRILE ACCEPTABLE.

EYE PROTECTION: SPLASH PROOF GOGGLES AND/OR FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT:

PROTECTIVE CLOTHING SUCH AS BUTYL, NEOPRENE, OR NITRILE RUBBER APRON ACCEPTABLE. A SAFETY SHOWER, AN EYE BATH, AND WASHING FACILITIES SHOULD BE AVAILABLE.

***** SECTION IX-SPECIAL PRECAUTIONS*****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

CONTAMINATED CLOTHING SHOULD BE WASHED BEFORE REUSE

DO NOT SAND, FLAME CUT, BRAZE OR WELD THE DRY COATING WITHOUT NIOSH APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

OBSERVE PRECAUTIONARY LABEL WARNINGS.

PREPARED BY R. A. PROKOP